Cold Water Hand Carry Electric Models

- Triplex plunger pump with ceramic plungers and stainless steel valves.
- 35' Power cord with ground fault interupter
- Adjustable pressure
- Chemical Injection
- Non-marking hose
- Trigger Gun
- 36" two piece wand
- Multi-reg zero to sixty degree pattern tip with Hi-Low for chemical injection
- Optional pumps handle fluids up to 180° degrees fahrenheit

1500A Models

1000A

1000-1500 Models

Model	PSI/bar	GPM/lpm	HP	Voltage /amp/phase	Pump Max. Temp.	Thermal	Dimensions L x W x H	Ship Weight
1000A	1000 / 69	2 / 7.6	1.5	120 Volt / 15 amp / 1	140° F	n/a	18" x 12" x 11"	50 lbs.
1500A	1450 / 100	2 / 7.6	2	120 Volt / 20 amp / 1	140° F	Mechanical	18" x 12" x 11"	68 lbs.
1500AC*	1450 / 100	2 / 7.6	2	120 Volt / 20 amp / 1	140° F	Mechanical	18" x 12" x 11"	68 lbs.
1000	1000 / 69	2.2 / 8.4	1.5	120 Volt / 15 amp / 1	140° F	Mechanical	18" x 12" x 14"	70 lbs.
1000C*	1000 / 69	2.2 / 8.4	1.5	120 Volt / 15 amp / 1	140° F	Mechanical	18" x 12" x 14"	70 lbs.
1500	1500 / 103.5	3 / 11.4	3	230 Volt / 20 Amp / 1	140° F	Mechanical	24" x 16" x 15"	98 lbs.
1500C*	1500 / 103.5	3 / 11.4	3	230 Volt / 20 Amp / 1	140° F	Mechanical	24" x 16" x 15"	98 lbs.
1500ADE	1450 / 100	2 / 7.6	2	120 Volt / 20 amp / 1	180° F	Electric Cut-out	18" x 12" x 11"	68 lbs.
1500ADS	1450 / 100	2 / 7.6	2	120 Volt / 20 amp / 1	180° F	Mechanical	18" x 12" x 11"	68 lbs.

*C denotes CSA approved model

Master Distributors: P.O. Box 141727 Grand Rapids, MI. 49514-1727