Cold Water MX Cart Electric Models

Shown above with accessory reel #GEN D30001

- Triplex plunger pump with ceramic plungers and stainless steel valves.
- 35' Power cord with ground fault interupter
- Adjustable pressure
- Chemical Injection
- 40' non-marking hose
- Trigger Gun
- Heavy duty wand with quick change tips in 0°,15°,25°,40° soap tip
- 36" two piece wand
- Totally enclosed motor
- Optional pumps handle fluids up to 180° degrees fahrenheit
- Powder coated frame with wand/hose rack and accessory hose mounting plate.
- 10" pneumatic tires with tube
- Chemical rack for two, one gallon jugs
- Dual chemical injection
- Add an accessory reel

Model	PSI/bar	GPM/lpm	HP	Voltage /amp/phase	Pump Max. Temp.	Thermal	Dimensions L x W x H	Ship Weight
1500AMX	1450 / 100	2 / 7.6	2	120 Volt / 20 amp / 1	140° F	Mechanical	32" x 22" x 39"	118 lbs.
1000MX*	1000 / 69	2.2 / 8.4	1.5	120 Volt / 15 amp / 1	140° F	Mechanical	32" x 22" x 39"	106 lbs.
1500MX*	1500 / 103.5	3 / 11.4	3	230 Volt / 20 Amp / 1	140° F	Mechanical	32" x 22" x 39"	122 lbs.
20005MX*	2000 / 138	3 / 11.4	5	230 Volt / 25 Amp / 1	140° F	Mechanical	32" x 22" x 39"	150 lbs.
1500AMXDS	1450 / 100	2 / 7.6	2	120 Volt / 20 amp / 1	180° F	Mechanical	32" x 22" x 39"	118 lbs.
1500AMXDE	1450 / 100	2 / 7.6	2	120 Volt / 20 amp / 1	180° F	Electric Cut-out	32" x 22" x 39"	118 lbs.
1000MXDS*	1000 / 69	2.2 / 8.4	1.5	120 Volt / 15 amp / 1	180° F	Mechanical	32" x 22" x 39"	106 lbs.
1000MXDE	1000 / 69	2.2 / 8.4	1.5	120 Volt / 15 amp / 1	180° F	Electric Cut-out	32" x 22" x 39"	106 lbs.
1500MXDS*	1500 / 103.5	3 / 11.4	3	230 Volt / 20 Amp / 1	180° F	Mechanical	32" x 22" x 39"	122 lbs.
20005MXDS*	2000 / 138	3 / 11.4	5	230 Volt / 25 Amp / 1	180° F	Mechanical	32" x 22" x 39"	150 lbs.

*C denotes approval for Canadian shipment

Master Distributors: P.O. Box 141727 Grand Rapids, MI. 49514-1727